



China 608 Bearing Supplier



NSK deep groove ball bearing 6212DDU NSK 6212 bearing

Bearing No. 6212DDU

6212DDU Bearing 2D drawings and 3D CAD models

| | |
|-------------------------------|--------------------------|
| Size | 60x110x22 mm |
| Bore Diameter | 60 mm |
| Outer Diameter | 110 mm |
| Width | 22 mm |
| d | 60 mm |
| D | 110 mm |
| B | 22 mm |
| C | 22 mm |
| r min. | 1,5 mm |
| da min. | 68 mm |
| da max | 74,5 mm |
| Da max. | 102 mm |
| ra max. | 1,5 mm |
| Weight | 0,783 Kg |
| Basic dynamic load rating (C) | 52,5 kN |
| Basic static load rating (C0) | 36 kN |
| (Grease) Lubrication Speed | 3 800 r/min |
| Category | Single Row Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | NSK |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.791 |
| EAN | 0029176064555 |
| Product Group | B00308 |
| Enclosure | 2 Seals |



China 608 Bearing Supplier

| | |
|---------------------------------|--|
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Enclosure Type | Contact Seal |
| Internal Clearance | C0-Medium |
| Inch - Metric | Metric |
| Long Description | 60MM Bore; 110MM Outside Diameter; 22MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage; |
| Other Features | Deep Groove Rubber Seal |
| Category | Single Row Ball Bearing |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer URL | http://www.nskamericas.com |
| Manufacturer Item Number | 6212DDU |
| Weight / LBS | 1.7265 |
| Bore | 2.362 Inch 60 Millimeter |
| Inner Race Width | 0 Inch 0 Millimeter |
| Outside Diameter | 4.331 Inch 110 Millimeter |
| Outer Race Width | 0.866 Inch 22 Millimeter |
| SRI | 8.22 |
| hidYobi | 6212DDU |
| | |



China 608 Bearing Supplier

| | |
|------------|-------------|
| LangID | 1 |
| D_ | 110 |
| SREX | 0.03 |
| B_ | 22 |
| da min | 68 |
| hidTable | ecat_NSRDGB |
| SRE | 8.22 |
| mass | 0.783 |
| GRS rpm | 3800 |
| ra | 1.5 |
| SRIX | 0.03 |
| D_a | 102 |
| SRIN | -0.03 |
| C0 | 36 |
| fo | 14.3 |
| SREN | -0.03 |
| DE_ | 102.375 |
| Prod_Type3 | DGBB_SR_DD |
| DA_ | 15.875 |
| bomp | 0 |
| Z_ | 10 |
| yobi | 6212DDU |
| C_conv | 52500 |
| ALPHA_ | 0 |
| SDM_ | 86.5 |
| r | 1.5 |
| KBRG | 6161 |
| SBRG | 2 |
| DI_ | 70.625 |